

▶ **608-384N D-Sub Contact Crimping Tool**

For female & male D-SUB miniature contacts.



Material	HRC	Handle	Crimp die profile	Application
AISI1050, DIE:AISI4140	45°±3°	PP		Non-insulated open barrel connectors & D-SUB V.35 contact pins
Crimp Size				OAL (mm) Individual packing
AWG 30-24/22-18 DIN 0.05-0.25/0.50-1.0 mm² JIS 0.05-0.25/0.35-0.9 mm²				205 Blister card

▶ **CP-462G Wire Ferrule Crimp Tool-Square Crimp**

- Adjustable ratchet and lever action construction reduces fatigue degree
- Special four-mandrel crimping style for square crimp.
- High quality crimping standard ensures repeatable crimping action.



Four-mandrel for square crimp



Material	HRC	Handle	Application	OAL (mm)	Individual packing
S44C	40°±2°	Nylon	Usable for cord end terminals AWG 26 ~ 10 DIN 0.25 ~ 6.0 mm² JIS 0.20 ~ 5.5 mm²	175	Blister card

▶ **CP-463 D-Sub Contact Crimping Tool**

- Ergonomic handle design provides low-effort operation
- Superior pull strength results
- High quality crimping standard ensures repetitive, reliable crimping action
- Adjustable pin height locator




4 Way to Crimping

Material	HRC	Handle	Application	OAL (mm)	Individual packing
SPCC + carbon steel	45°±3°	PVC	Crimping of closed-barrel RS-232 D-sub contacts. AWG 20-12 / DIN 0.5-4.0 mm² JIS 0.5-3.5 mm²	165	Blister card

▶ **608-400 4 Way Indent Crimping Tool**

- Used to crimp closed barrel, screw machine pin and socket style contacts.
- Performs a simultaneous 4 indent crimp for superior contact retention.



4 Way to Crimping



Material	HRC	Handle	Application	OAL (mm)	Individual packing
S50C	45°±3°	PVC	Crimping of closed-barrel RS-232 D-sub contacts. AWG 26-20 DIN 0.2-0.5 mm² JIS 0.2-0.5 mm²	162	Blister card

▶ **8PK-CT004 Insertion/Extraction Tool**

- RS232 insertion & extraction use
- Red: insertion PIN
- White: extraction PIN



Body	Handle	OAL (mm)	Individual packing
Metal	PP	102	Pouch

▶ **1PK-CT007 Double End Socket Can Wrench**

- Uses to place fuses in cable terminals and connect wires to fuses and binding posts.
- 3/8" & 7/16" hex double end. Plastic handle.



Material	Handle	HRC	O.A.L (mm)	Individual packing
S45C	Plastic	45°±3°	180	Blister card