


Клеммы тип "О" неизолированные



Размеры в таблице указаны в мм

Наименование	Диаметр отверстия D	Ширина W	Сечение кабеля	
			AWG	mm ²
TR-1.25-3	3.7	5.5	22-16	0.5-1.5
TR-1.25-4	4.3	8.0	22-16	0.5-1.5
TR-1.25-5	5.3	8.0	22-16	0.5-1.5
TR-1.25-6	6.4	11.7	22-16	0.5-1.5
TR-1.25-8	8.4	11.7	22-16	0.5-1.5
TR-1.25-10	10.5	13.7	22-16	0.5-1.5
GRNB 1.25-10	10.5	13.7	22-16	0.5-1.5
RNBS -2-3.5	3.2	6.5	16-14	1.5-2.5
TR-2-3	3.7	6.5	16-14	1.5-2.5
TR-2-4	4.3	8.5	16-14	1.5-2.5
TR-2-5	5.3	9.5	16-14	1.5-2.5
TR-2-6	6.4	12.0	16-14	1.5-2.5
GRNB-2-6	6.4	12.0	16-14	1.5-2.5
TR-2-8	8.4	12.0	16-14	1.5-2.5
TR-2-10	10.5	13.7	16-14	1.5-2.5
TR-3.5-4	4.3	8.0	14-12	2.5-4.0
TR-3.5-5	5.3	8.0	14-12	2.5-4.0
TR-3.5-6	6.4	12.0	14-12	2.5-4.0
TR-3.5-8	8.4	15.0	14-12	2.5-4.0
TR-3.5-10	10.5	15.0	14-12	2.5-4.0
TR-5.5-4	4.3	9.5	12-10	4.0-6.0
TR-5.5-5	5.3	9.5	12-10	4.0-6.0
TR-5.5-6	6.4	12.0	12-10	4.0-6.0
GRNB-5.5-6	6.4	12.0	12-10	4.0-6.0
TR-5.5-8	8.4	15.0	12-10	4.0-6.0
TR-5.5-10	10.5	15.0	12-10	4.0-6.0
TR-8-5	5.3	9.0	8	10.0
TR-8-6	6.4	12.0	8	10.0
TR-8-8	8.4	15.0	8	10.0
TR-8-10	10.5	15.0	8	10.0