


DATA SHEET



BYV95 series Fast soft-recovery controlled avalanche rectifiers

Product specification
Supersedes data of April 1982

1996 Jun 07

Fast soft-recovery controlled avalanche rectifiers

BYV95 series


FEATURES

- Glass passivated
- High maximum operating temperature
- Low leakage current
- Excellent stability
- Guaranteed avalanche energy absorption capability
- Available in ammo-pack.

DESCRIPTION

Rugged glass SOD57 package, using a high temperature alloyed construction. This package is

hermetically sealed and fatigue free as coefficients of expansion of all used parts are matched.



LIMITING VALUES

In accordance with the Absolute Maximum Rating System (IEC 134).

SYMBOL	PARAMETER	CONDITIONS	MIN.	MAX.	UNIT
V _{RRM}	repetitive peak reverse voltage				
	BYV95A		–	200	V
	BYV95B		–	400	V
	BYV95C		–	600	V
V _R	continuous reverse voltage				
	BYV95A		–	200	V
	BYV95B		–	400	V
	BYV95C		–	600	V
I _{F(AV)}	average forward current	T _{tp} = 65 °C; lead length = 10 mm see Fig. 2; averaged over any 20 ms period; see also Fig. 6	–	1.5	A
		T _{amb} = 65 °C; PCB mounting (see Fig.11); see Fig. 3; averaged over any 20 ms period; see also Fig. 6	–	0.8	A
I _{FRM}	repetitive peak forward current	T _{tp} = 65 °C; see Fig. 4	–	17	A
		T _{amb} = 65 °C; see Fig. 5	–	9	A
I _{FSM}	non-repetitive peak forward current	t = 10 ms half sine wave; T _j = T _{j max} prior to surge; V _R = V _{RRMmax}	–	35	A
E _{RSM}	non-repetitive peak reverse avalanche energy	L = 120 mH; T _j = T _{j max} prior to surge; inductive load switched off	–	10	mJ
T _{stg}	storage temperature		–65	+175	°C
T _j	junction temperature	see Fig. 7	–65	+175	°C

Fast soft-recovery controlled avalanche rectifiers

BYV95 series

ELECTRICAL CHARACTERISTICS

$T_j = 25\text{ °C}$ unless otherwise specified.

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT	
V_F	forward voltage	$I_F = 3\text{ A}$; $T_j = T_{j\text{ max}}$; see Fig. 8	–	–	1.35	V	
		$I_F = 3\text{ A}$; see Fig. 8	–	–	1.60	V	
$V_{(BR)R}$	reverse avalanche breakdown voltage	$I_R = 0.1\text{ mA}$					
			BYV95A	300	–	–	V
			BYV95B	500	–	–	V
	BYV95C	700	–	–	V		
I_R	reverse current	$V_R = V_{RRM\text{ max}}$; see Fig. 9	–	–	1	μA	
		$V_R = V_{RRM\text{ max}}$; $T_j = 165\text{ °C}$; see Fig. 9	–	–	150	μA	
t_{rr}	reverse recovery time	when switched from $I_F = 0.5\text{ A}$ to $I_R = 1\text{ A}$; measured at $I_R = 0.25\text{ A}$; see Fig. 12	–	–	250	ns	
C_d	diode capacitance	$f = 1\text{ MHz}$; $V_R = 0\text{ V}$; see Fig. 10	–	45	–	pF	
$\left \frac{dI_R}{dt} \right $	maximum slope of reverse recovery current	when switched from $I_F = 1\text{ A}$ to $V_R \geq 30\text{ V}$ and $dI_F/dt = -1\text{ A}/\mu\text{s}$; see Fig. 13	–	–	7	$\text{A}/\mu\text{s}$	

THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	CONDITIONS	VALUE	UNIT
$R_{th\ j\text{-tp}}$	thermal resistance from junction to tie-point	lead length = 10 mm	46	K/W
$R_{th\ j\text{-a}}$	thermal resistance from junction to ambient	note 1	100	K/W




Note

1. Device mounted on an epoxy-glass printed-circuit board, 1.5 mm thick; thickness of Cu-layer $\geq 40\text{ }\mu\text{m}$, see Fig. 11. For more information please refer to the "General Part of associated Handbook".

Fast soft-recovery
controlled avalanche rectifiers




BYV95 series

GRAPHICAL DATA







Fast soft-recovery
controlled avalanche rectifiers

BYV95 series





Fast soft-recovery
controlled avalanche rectifiers

BYV95 series



Fast soft-recovery
controlled avalanche rectifiers


BYV95 series



Fast soft-recovery
controlled avalanche rectifiers

BYV95 series

PACKAGE OUTLINE



DEFINITIONS

Data Sheet Status	
Objective specification	This data sheet contains target or goal specifications for product development.
Preliminary specification	This data sheet contains preliminary data; supplementary data may be published later.
Product specification	This data sheet contains final product specifications.
Limiting values	
Limiting values given are in accordance with the Absolute Maximum Rating System (IEC 134). Stress above one or more of the limiting values may cause permanent damage to the device. These are stress ratings only and operation of the device at these or at any other conditions above those given in the Characteristics sections of the specification is not implied. Exposure to limiting values for extended periods may affect device reliability.	
Application information	
Where application information is given, it is advisory and does not form part of the specification.	

LIFE SUPPORT APPLICATIONS

These products are not designed for use in life support appliances, devices, or systems where malfunction of these products can reasonably be expected to result in personal injury. Philips customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Philips for any damages resulting from such improper use or sale.